

REMOVABLE POLYETHYLENE TAPE

Venture Tape 1499 is a 4.0 mil (100 micron), strong and conformable polyethylene film tape coated with a specially formulated, high tack, removable acrylic non-curing adhesive system. This product is easily hand tearable in both directions and has resistance to moisture, acids, chemicals, alkalis, oils, abrasion, and weathering.

Product Construction



Features & Benefits

- Strong, conformable polyethylene offers excellent protection for windows, doors and other surfaces
- Excellent temperature resistance; performs well over a wide range of environmental conditions
- High tack, removable acrylic adhesive provides secure bond with no residue on removal
- Easily hand tearable film
- In stock product available for immediate delivery

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness	5.0 mils	0.13 mm	PSTC-133
Peel Adhesion ^Δ	15 oz/in	4.2 N/25 mm	PSTC-101
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @ 15.2 kPa	PSTC-107
Tensile Strength	11 lb/in	48.8 N/25 mm	PSTC-131
Elongation	450 %	450 %	PSTC-131
Service Temperature	-40 to 175 °F	-40 to 79 °C	

^Δ - 20 minute dwell

Typical values are not intended to be used for specification development. Technical data is believed to be true and accurate; Venture Tape recommends that the purchaser test for fitness of use in all applications.

Product Configurations

- Standard roll sizes and custom rolls available on request

Contact Venture Tape today for a complete list of products or a free sample

Toll Free North America 800-343-1076

From United Kingdom 0-800-962-957

From Australia 1-800-122-797

www.venturetape.com

VentureTape®

GTA - NHT, Inc.
 Venture Tape
 30 Commerce Rd., Rockland, MA 02370
 Tel 781-331-5900; Fax 781-871-0065
 800-343-1076 (U.S.A.), 800-544-1024 (Canada)
 Toll Free Fax 877-264-5490
www.venturetape.com

GTA

TAPES & ADHESIVES
 a 3M Company